



MATERIAL:

NO	NAME	Q'TY	MATERIAL	DESCRIPTION	REMARKS
1	SEALING	1	SYNTHETIC RUBBER	Yellow	
2	HOUSING	1	SYNTHETIC RESIN	BLACK	
3	CONTACT	7	COPPER ALLOY	PLATING GOLD	
4	PLATE	1	SYNTHETIC RESIN	BLACK	
5	SCREW	2	STEEL	M2-0.4*4	BLACK

PART NUMBER:

NO	PART NO	REV	MATERIAL	DESCRIPTION
1	6353C-07B-AA-N00	A0	SEE NOTE	JM30伺服电机编码器焊线底座7P/小型斜口
2	6353C-07B-AA-N01	A0	SEE NOTE	JM30伺服电机编码器焊线底座7P/小型斜口/无螺丝

NOTE:
Physical

- Insulation Material: Synthetic Resin UL94V-0
Color: Black
- Contact Material: Copper Alloy
Plating: Nickel For all
Contact Area: Gold
Termination Area: Glod flash

Electrical

- Current Rating: 1A Max.
- Voltage Rating: 100 VAC.
- Insulation Resistance: >1000 MΩ at @500VDC
- Withstanding Voltage: 1500VAC for 1 minute
- Contact Resistance: 10 mΩ MAX

Environmental

- Operating Temperature: -40°C to +105°C
- Solder Temperature: 255~265°C for 5~10 sec.

OPERATION		DRAW	Tim Chu	2022.11.11	SCALE	FIT
X.X	±0.30					
X.XX	±0.20	CHECK	Ou Yang	2022.11.11	SIZE	A4
X.XXX	±0.10				SHEET	1/2
Angle	±3°	APPROVE	Wang Wei	2022.11.11	PROJ.	◆
DIM	TOL					

JILN® 深圳市锦凌电子有限公司
SHENZHEN JINLING ELECTRONIC CO.,LTD
Tel: 86-755-2997-5806/5802 Fax: 86-755-2997-5992

PART NO.	6353C-07B-AA-N00
TITLE:	JM30伺服电机编码器焊线底座7P/小型斜口

NO	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2022.11.11	NEW DRAWING	

1 2 3 4 5 6 7 8 9